



N  
 1/4" = 1'-0"  
 Reflected Ceiling Plan - First Floor

### Ceiling Plan Keynotes

1. PROVIDE BOXED BLOCKING FOR TELEVISION BRACKET IN CEILING. VERIFY LOCATION W/ EQUIPMENT SUPPLIER. TV TO BE PROVIDED BY TENANT. SEE DETAIL A15 / D2.
2. PROVIDE BOXED BLOCKING FOR DENTAL LIGHT. VERIFY EXACT LOCATION WITH EQUIPMENT SUPPLIER. SEE DETAIL A17 / D2
3. ONE HOUR CEILING. SEE DETAIL A18 / D-1, PARTITION D FOR CONSTRUCTION.
4. PROVIDE 6" SOUND BATT INSULATION OVER TOP OF CEILING THIS ROOM.
5. BOTTOM OF PENDANTS WITH INTERIOR DESIGNER, TYPICAL ALL PENDANTS., VERIFY HEIGHT WITH PENDANTS CHOSEN BY CLIENT.
7. J-BOX LOCATION FOR CEILING FAN. PROVIDE SUPPORT FOR MIN. 75 LBS.
8. CENTER LIGHT IN ROOM, TYPICAL
9. CENTER SCONCE ON SINK, COORDINATE WITH PLUMBER TO AVOID CONFLICT WITH VENT
10. CENTER PENDANT ON BOTH SIDES OF MIRROR
11. UPSIDE DOWN CANOE WITH VINTAGE LIGHTING, PROCURED BY DESIGNER
12. CENTER EXHAUST FAN OVER WATERCLOSET.
13. SPECIALTY LED DISK LIGHTING
14. SPECIALTY LED PANELS IN SUSPENDED 2X4 GRID
15. LINEAR DIFFUSER IN FACE OF SOFFIT
16. SPOT DIFFUSER IN FACE OF SOFFIT/WALL
17. FOAM BOAT DESIGN BY DESIGNER
18. FOAM LEAF/TREE DESIGN BY DESIGNER
18. STACKED LIGHT COVE WITH LED LIGHTING
19. PERIMETER COVE WITH LED LIGHTING
20. 16"x2" SUSPENDED PLANKS BELOW GYP BOARD CEILING TO BOTTOM OF DECK
21. FLOATING FRAMED DRYWALL FINISHED CLOUD

14. PROVIDE ONE AUTOMATIC FIRE SPRINKLER HEAD IN MEDGAS ROOM FOR COOLING OF TANKS IN CASE OF FIRE.

### Ceiling Legend

-  SUSPENDED ACOUSTICAL TILE CEILING  
 ARMSTRONG DUNE  
 24X24, 15/16 GRID, REGULAR, WHITE  
 SEE DETAIL A13/D2 FOR GRID BRACING
-  HARD LID CEILING/SOFFIT  
 LEVEL 4 - SMOOTH TEXTURE  
 PAINT: MATCH ADJACENT WALL PAINT  
 EGGSHELL FINISH.  
 SEE DETAIL A11/D2 FOR TYPICAL BRACING

### Fixture Legend - Mechanical

SYMBOL	DESCRIPTION
	TITUS ONE/TWO/THREE SLOT LINEAR DIFFUSER/RETURN, TYP 4, WHITE
	TITUS OMNI DIFFUSER/RETURN, 24X24 WHITE
	TITUS TMS, 24X24 DIFFUSER/RETURN WHITE
	SEIHO TT MINI ADJUSTABLE CEILING DIFFUSER 8" Ø
	SEIHO PK SPOT DIFFUSER - ALUMINUM MILL FINISH 16"Ø
	SEIHO NTX TURBONOZZLE- ALUMINUM MILL FINISH 16"Ø
	EXHAUST FAN - SEE MECHANICAL SHEET FOR TYPE AND SPECIFICATION

### General Notes

- A. VERIFY GRID LAYOUT AND CENTERING PRIOR TO INSTALL.
- B. VERIFY PLACEMENT OF ALL LIGHTS AND DIFFUSERS WITH TENANT AND EQUIPMENT SUPPLIER.
- C. RECESSED CAN LIGHTING TO BE CENTERED IN ACOUSTICAL TILE CEILING, U.N.O
- D. SEE LIGHTING SCHEDULE SHEET E-2 FOR FIXTURE TYPES.
- E. SUSPENDED ACOUSTICAL TILE CEILING TO BE INSTALLED IN ACCORDANCE WITH ASTM C 635 AND ASTM C 636.